

THE IDEAL SYSTEM FOR Energy efficient buildings.

1300 ALSPEC (1300 257 732) alspec.com.au




# **Centre Pocket Double Glazed Framing**

The ecoFRAMEplus is the ideal system principally when energy efficiency is paramount. Its versatility allows countless specifications to be achieved, from standard shopfront applications, through to the most challenging structural and energy requirements.

Available in a frame depth of 101.6mm x 50mm and 150mm x 50mm, ecoFRAMEplus allows a frame to transform from double to single glazed with ease. Glazing could not be simpler with the colour coded wedges to deal with the many diverse glass options.

Sub sills are recommended for optimum weathering with all ecoFRAMEplus systems.

## **Typical Configurations**



### **CAD Cross Sections**



### **Key Features**

- Sharp unbroken lines
- 4mm 14mm single glazed and up to 28mm double glazed options
- Robust frame
- Secure glazing using fully captive backing gaskets to outside of window frame
- Excellent weathering performance
- Colour coded glazing wedges for ease of identification
- Easily adapts to Alspec's awnings and hinged doors

### **Technical Specifications**

Frame Dimensions		
Option 1	101.6 x 50mm	
Option 2	150 x 50mm	
Maximum Recommended Sizes	101.6mm Frame	150mm Frame
Height	4200mm	4800mm
Width	2400mm	2400mm
Maximum Product Performance	101.6mm Frame	150mm Frame
SLS (Pa)	2000	2500
ULS (Pa)	3000	3800
Water (Pa)	1000	1200
Acoustic Performance	101.6mm Frame	150mm Frame
Glass Type	Rw (C; C <sub>tr</sub> )	Rw (C; C <sub>tr</sub> )
6.38mm Laminate	32 (-1,-2) dB	32 (-1,-2) dB
6.38mm/ 12/ 6.38mm IGU	36 (-1,-5) dB	36 (-1,-5) dB
Glazing Details (both)		
Glass Position	Centre	
Single Glazed	4 - 14mm	
Double Glazed	16 - 28mm	
Thermal Performance	101.6mm Frame	150mm Frame
Uw range DG	2.5 - 3.5	3.1 - 3.7
Uw range DG SHGC range DG	2.5 - 3.5 0.18 - 0.64	3.1 - 3.7 0.15 - 0.64
-		
SHGC range DG	0.18 - 0.64	0.15 - 0.64
SHGC range DG Compatible Systems	0.18 - 0.64 mercial Shopfro	0.15 - 0.64
SHGC range DG Compatible Systems Swan Evo 45mm Com	0.18 - 0.64 mercial Shopfro	0.15 - 0.64
SHGC range DG Compatible Systems Swan Evo 45mm Comm Torrens 45mm Comme	0.18 - 0.64 mercial Shopfron ercial Shopfront	0.15 - 0.64 ont Door Door
SHGC range DG Compatible Systems Swan Evo 45mm Com Torrens 45mm Comme 35/50mm Awning Wir	0.18 - 0.64 mercial Shopfro ercial Shopfront adow	0.15 - 0.64 ont Door Door
SHGC range DG Compatible Systems Swan Evo 45mm Comm Torrens 45mm Comme 35/50mm Awning Wir ProTilt High Performar	0.18 - 0.64 mercial Shopfront adow ace Awning/Cas bance Sliding Do	0.15 - 0.64 ont Door Door



#### 101.6mm frame















